First Round: 2010 1-hour SO₂ NAAQS Nonattainment Area Modeling

Summary

Staff has completed preliminary modeling for Missouri's two SO₂ nonattainment areas (NAA): Jefferson County and Jackson County. Based on the results from these models runs, staff has identified 12 sources with a contributing impact on the nonattainment area. It should be noted that two of the 12 sources are located in Kansas.

An individual email will be sent to each facility in Table 1 and Table 2 as an initial contact. The email will contain source information specific to each facility and will request confirmation of the information from the facility.

Table 1: Summary of facilities in the Jefferson County NAA with maximum impacts greater than the established background (based on actual emissions from 2012 EIQ)

| Facility | Max Impact (μg/m³) | Anticipated Applicable Federal Regulations | | |
|------------------------|--------------------|---|--|--|
| Ameren Meramec* | 298.99 | MATS | | |
| Ameren Rush Island* | 255.17 | MATS | | |
| River Cement ** | 108.5 | Undetermined | | |
| Ameren Labadie* | 67.057 | MATS | | |
| Mississippi Lime | 47.9 | Boiler MACT | | |
| St. Gobain Containers | 33.18 | Boiler MACT | | |
| Established Background | | 23.58 μg/m ³ | | |
| 2010 1-hour SO2 NAAQS | (75 ppb) | Equivalent to 196.5 μg/m ³ | | |

^{*} Continuous Emissions Monitoring data available for only certain individual emission units.

Table 2: Summary of facilities in the Jackson County NAA with maximum impacts greater than the established background (based on actual emissions from 2012 EIQ)

| Facility | Max Impact (μg/m³) | Anticipated Applicable Federal Regulations | | |
|------------------------|--------------------|--|--|--|
| Veolia Energy | 392.97 | Boiler MACT | | |
| KCPL Hawthorn* | 75.47 | MATS | | |
| IPL Blue Valley* | 69.44 | MATS | | |
| BPU Quindaro (KS)* | 56.67 | MATS | | |
| BPU Nearman (KS)* | 36.17 | MATS | | |
| KCPL Sibley* | 35.24 | MATS | | |
| Established Background | and the second | $34.06 \mu \text{g/m}^3$ | | |
| 2010 1-hour SO2 NAAQS | (75 ppb) | Equivalent to 196.5 μg/m ³ | | |

^{*} Continuous Emissions Monitoring data available for only certain individual emission units.

^{**} Currently being reviewed for source parameter accuracy.

Summary Details

A modeling protocol, describing the meteorological data used in the model and outlining the methodology used in our modeling approach, was prepared by staff and submitted to the EPA on Oct. 23, 2013 for review. AERMOD is the dispersion model used to determine compliance with the NAAQS. For this round of attainment demonstrations, compliance with the NAAQS was evaluated only in the nonattainment areas. As such, the receptor grid is contained exclusively within the NAA boundaries.

The impact of sources within the nonattainment area and within 50 km of the nonattainment area was evaluated. A buffered approach was developed to determine the source inventory for each nonattainment area. This approach (Table 3) used proximity to the nonattainment area, actual reported emissions, and calculated potential emissions as indicators for inclusion in the model inventory.

Table 3: Summary of buffered approach

| Buffer level | Sources for inclusion in the inventory | | | |
|--|---|--|--|--|
| Nonattainment Area | All SO2 sources | | | |
| < 10 km from the NAA boundary | Sources with a PTE > 100 tpy | | | |
| between 10 & 50 km from the NAA boundary | Sources with actual emissions > 100 tpy | | | |

Initial Base Run

In the initial run, sources were modeled using their annual reported emissions and release parameters, as reported in MOEIS. For Electric Generating Units (EGUs) that are required to use a Continuous Emissions Monitoring System (CEMS) and report those to the EPA's Clean Air Markets Division (CAMD) database, the CEMS data was used in lieu of actual reported MOEIS data. The 95th percentile of total emissions was chosen as the hourly emission rate in the model to exclude extreme anomalies that do not necessarily represent maximum emissions associated with peak loads at worst-case operating conditions.


A representative background concentration value [see value in Tables 1 & 2] was established for each area based on data obtained from area monitors. This background value accounts for any natural emissions as well as sources not explicitly included in the model inventory.

Results from the initial model run were analyzed to determine which facilities had a contributing impact within the nonattainment area. For this initial analysis, contributing impact is defined as having an impact greater than the established background concentration.

Future Considerations

Federal regulations such as the Mercury and Air Toxics Standards (MATS) MACT and the Boiler MACT may provide SO₂ emission reductions that could be applied in the attainment demonstrations. The MATS MACT includes an alternative SO₂ limit in place of the Hydrogen Chloride (HCl) limits for qualifying EGUs. The Boiler MACT allows the use of SO₂ CEMS for demonstrating compliance with HCl emission limits, with special conditions. Co-benefits for potential SO₂ emission reductions associated with controlling Hazardous Air Pollutant (HAP) emissions, specifically acid gas HAPs, are expected from units subject to the Boiler MACT. Certain provisions of both the MATS [40 CFR 63 Subpart 5U] and the Boiler MACT [40 CFR 63 Subpart 5D] are currently being reconsidered or proposed for amendment.

Jefferson County NAA with Buffers and Initial Model Run Contributing Impact Sources






Division of Environmental Quality Air Pollution Control Program Prepared: October 29, 2013

Legend

| • | Impacting Sources (As shown in | List) | Jefferson | 10 km Buffe |
|---|--------------------------------|-------|-----------|-------------|
| | Jefferson 50 km Buffer | | Jefferson | County NAA |

Jackson County NAA with Buffers and Initial Model Run Contributing Impact Sources





Division of Environmental Quality Air Pollution Control Program Prepared: October 29, 2013

Legend

| 0 | Impacting Sources (As shown in List) | Jackson | 10 km Buffe |
|---|--------------------------------------|---------|-------------|
| | Jackson 50 km Buffer | Jackson | County NAA |